

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,268,503 B2
APPLICATION NO. : 10/508992
DATED : September 11, 2007
INVENTOR(S) : Yamasaki et al.

Page 1 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Please replace claim 1 with the following:

1. A vibration linear actuating device comprising a vibrating linear actuator and a driver for driving the actuator; the vibrating linear actuator including:

- (a) a mover having a permanent magnet magnetized in a radial direction
- (b) a stator having a coil and facing the permanent magnet; and
- (c) an elastic body for coupling the stator to the mover and energizing the mover toward a center of the stator; the driver including:
- (d) a driving section having a switching element for powering the coil;
- (e) and output controller for controlling the switching element; and
- (f) a zero-cross detector for detecting a zero-cross point of back electromotive force (BEMF) generated in the coil and outputting a zero-cross signal;

wherein the driver transmits the zero-cross signal to the output controller and powers the coil in one direction for vibrating the mover in corporation with the elastic body,

characterized by

- (g) a zero-cross monitor interposed between the zero-cross detector and the output controller, the zero-cross monitor monitoring the zero-cross signal and prohibiting acceptance of a next zero-cross signal for a given time after input of the zero-cross signal.

Please replace claim 2 with the following:

2. The vibration linear actuating device of claim 1, wherein the driver transmits a re-starter signal to the output controller when the zero-cross signal is halted for a given time.

Please replace claim 3 with the following:

3. The vibration linear actuating device of claim 1, wherein the zero-cross detector is coupled to the coil via a BEMF amplifier and a level-shift section.

Please replace claim 4 with the following:

4. The vibration linear actuating device of claim 1, wherein the driver further includes a timing adjuster disposed between the zero-cross detector and the output controller.

Please replace claim 5 with the following:

5. The vibration linear actuating device of claim 4, wherein the timing adjuster includes a phase locked loop.

Please replace claim 6 with the following:

6. The vibration linear actuating device of claim 1, wherein the output controller includes a pulse width modulator.

Please replace claim 7 with the following:

7. A method of driving a vibrating linear actuator, the actuator comprising:
a mover having a permanent magnet magnetized in a radial direction;
a stator having a coil and facing the permanent magnet; and
an elastic body for coupling the stator to the mover and energizing the mover toward a center of the stator, the method comprising the steps of:
(a) determining a zero-cross point of back electromotive force generated in the coil;
(b) determining a period for powering the coil in every cycle;
(c) determining a period for powering the coil at starting time;
(d) counting step (b) based on the determined result of step (a); characterized by the additional step of
(e) starting to count depending on the judging result at step (a), wherein the judging result at step (a) is kept invalidated until counting up at step (e).

Please replace claim 8 with the following:

8. The method of driving a vibrating linear actuator of claim 7 further comprising step (f) for counting for itself based on the determined result of step (a), wherein step (c) starts counting when step (f) counts up.

Please replace claim 9 with the following:

9. The method of driving a vibrating linear actuator of claim 8, wherein step (f) is reset depending on a next determined result.

Please replace claim 10 with the following:

10. A portable information apparatus comprising:
(a) a board;
(b) a vibrating linear actuator mounted to the board; the actuator including:
(b-1) a mover having a permanent magnet magnetized in a radial direction;
(b-2) a stator having a coil and facing the permanent magnet; and
(b-3) an elastic body for coupling the stator to the mover and energizing the mover toward a center of the stator;
(c) a driver mounted to the board, the driver including:
(c-1) a driving section having a switching element for powering the coil;
(c-2) an output controller for controlling the switching element; and
(c-3) a zero-cross detector for detecting a zero-cross point of back electromotive force (BEMF) generated in the coil and outputting a zero-cross signal;
wherein the driver transmits the zero-cross signal to the output controller and powers the coil in one direction for vibrating the mover in corporation with the elastic body,
characterized by
(c-4) a zero-cross monitor interposed between the zero-cross detector and the output controller,
the zero-cross monitor monitoring the zero-cross signal and prohibiting acceptance of a next zero-cross signal for a given time after input of the zero-cross signal.

Please replace claim 11 with the following:

11. The portable information apparatus of claim 10, wherein the vibrating linear actuator generates vibrations with a maximum amplitude in a vertical direction to the board.

Please replace claim 12 with the following:

12. The portable information apparatus of claim 10, wherein the driver transmits a re-starter signal to the output controller when the zero-cross signal is halted for a given time.

Please replace claim 13 with the following:

13. The portable information apparatus of claim 10, wherein the zero-cross detector is coupled to the coil via a BEMF amplifier and a level-shift section.

Please replace claim 14 with the following:

14. The portable information apparatus of claim 10, wherein the driver further includes a timing adjuster disposed between the zero-cross detector and the output controller.

Please replace claim 15 with the following:

15. The portable information apparatus of claim 14, wherein the timing adjuster includes a phase locked loop.


Please replace claim 16 with the following:

16. The portable information apparatus of claim 10, wherein the output controller includes a pulse width modulator.

Cancel claims 17-21.

Signed and Sealed this

Twenty-third Day of March, 2010

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, flowing style.

David J. Kappos
Director of the United States Patent and Trademark Office